

Buitenunit		UUA1 UL0	UUB1 U20	UUC1 U40	UUD3 U30
Artikelnummer buitenunit		<b>459.601</b>	<b>459.602</b>	<b>459.603</b>	<b>459.605</b>
Prijs buitenunit	€	<b>2.185,00</b>	<b>2.505,00</b>	<b>3.400,00</b>	<b>5.045,00</b>
Chassis code		UL2	U24A	U3	U3
Luchtdebiet hoog	M³/h	1.920	3.000	3.480	6.600
Geluidsdrukniveau <sup>(3)</sup> Max.	dB(A)	52	52	52	54
Geluidsvermogen Max.	dB	65	63	68	68
Afmetingen (BxDxH)	mm	770x288x545	870x330x650	950x330x834	950x330x1.380
Gewicht	kg	33,3	44,5	57.7	85

Elektrische gegevens					
Voeding	Ø/V/Hz	1/230/50	1/230/50	1/230/50	3/400/50
Opgenomen vermogen koelen (Nom.)	kW	0,97	1,56	1,94	4,35
Opgenomen vermogen verwarmen (Nom.)	kW	1,12	1,66	2,00	4,82
Stroom opname koelen / verwarmen (Nom. / Max.)	A	4,3 / 5,0	7,1 / 7,5	8,6 / 8,8	5,8 / 6,4
Voedingskabel naar		Buitenunit	Buitenunit	Buitenunit	Buitenunit
Afzekerwaarde	A	C15	C16	C25	C16
Bekabeling tussen binnen / buitenunit	Q x mm²	4 x 1,0	4 x 1,0	4 x 1,0	4 x 1,0

Koeltechnisch					
Koelleiding diameter vloeistof	mm(inch)	6,35(1/4)	6,35(1/4)	9,52(3/8)	9,52(3/8)
Koelleiding diameter gasleiding	mm(inch)	9,52(3/8)	12,7 (1/2)	15,88 (5/8)	15.88 (5/8)
Min./Max. leidinglengte	Mtr.	5,0 / 20,0	5,0 / 30,0	5,0 / 50,0	5,0 / 85,0
Max. hoogteverschil binnen / buitenunit	Mtr.	15	30	30	30
Nominale koudemiddelvulling	kg	0,90	1,10	1,60	3,00
Standaard voorgevuld tot	Mtr.	7,5	7,5	7,5	7,5
Bijvulling per meter	gram	20	20	40	40
GWP		675	675	675	675
T-CO <sub>2</sub> Equivalent		0,675	0,81	1,283	2,03